

KPLT-4H1200 LED

Powered by KUBOTA®

KEYPOWER®
Anytime Anywhere, Power Solutions



DIESEL FUEL



PORTABLE



LED LIGHT



LOW-NOISE




CERTIFICATION



ISO 9001

MODEL		KPLT-4H1200 LED
	Type of lights	LED Light
	Light model	TBA
	Light's fixture	Rectangle
	Luminous flux (LM)	39000 LM/light
	Number & power of lights	4x300 W
	Number of mast sections	7
	Mast extension	Hydraulic
	Mast rotation	359° Manual rotation with self locking
	Light tilt	Electrical

Dimension and Weight



DIMENSION		KPLT-4H1200 LED
	Length	3500mm
	Width	1620mm
	Height	2460 mm
	Full extending Height	9m
	Genset power	6 kW
	Gross weight	1360kg

KEYPOWER has the right to modify any feature without prior notice. Weights and dimensions based on standard products. Illustrations may include optional equipment. Technical data described in this catalogue correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product. Industrial design under patent.

KPLT-4H1200 LED

Powered by KUBOTA®

KEYPOWER®
Anytime Anywhere, Power Solutions

KPLT-4H1200 LED

FUEL TANK CAPACITY



120L

RUNTIME



190
HOURS

OPERATION



IN EXTREME
ENVIRONMENT

FUEL CONSUMPTION



0.7
L/H

LUMEN



39,000
LM
X4

STANDARD FEATURE



Hydraulic
winch
vertical
mast

LOW-NOISE



72
dBA@7m

LOADING



40'HC
container
16
units

Technical Specifications

ENGINE	KUBOTA®
Engine model	D1105
Speed (rpm)	1500/1800
Number of cylinders	3
Engine characters	4 cycles, Water-cooled diesel
Combustion System	E-TVCS
Engine aspiration	Naturally aspirated

TRAILER	
Trailer suspension & axle with brakes	Leaf springs axle without brake
Tow bar	Retractable & adjustable supporting wheel tow bar
Stabilizing legs & number	4 pcs drawbar with manual jacks
Wheel's rim size & tires	16" rim with regular tires
Tow adapter	2" or 50 mm ball adapter
Tail lights	Brake lights
Max towing speed	80 km/h

ALTERNATOR	
Standard configuration	Mecc alte LT3N-130/4
Frequency (HZ)	50/60
Rating voltage (50/60Hz)	230V (50HZ), 240V (60HZ) AC
Alternator insulation	Class H
Alternator protection grade	IP23

ADDITIONAL FEATURES	
Fuel tank Type	Double-deck tank
Fuel tank capacity	120 liters
Operating hours with all lights on	190 hours
Operating hours with full load	48 hours
Generator starting type or controller	HGM1790 (SMARTGEN)
Power outlet sockets	1 unit of Euro standard 16A/220V single phase power outlet socket
Max. against wind when fully extended	20 m/s
Noise level	72dB (A) at 7 meters away

+86 591 83405668
+86 591 38207503

info@keypower.com

www.keypower.com

Fuzhou Gff Keypower Equipment Company Limited
Keypower Solutions (Fujian) Company Limited

Add: No. 3-1, Dongling RD, Ganzhe Street, Minhou County, Fuzhou, Fujian, China